




PROJECT	DATE
TYPE	CATALOG #

NEPTUNE

H20-502B

KEY FEATURES

- HEAVY CAST BRASS
- ADJUSTABLE FOR PRECISE LIGHT PROJECTION
- 25 FT UNDERWATER RATED SJ CABLE WIRE
- 50 FT & 100 FT SJ CABLE WIRE OPTIONS
- DIMMABLE*
- HIGH TEMPERATURE SOCKET
- FIELD REPLACEABLE LED



PRODUCT SPECIFICATION

MATERIAL	CAST BRASS
FINISH	NATURAL BRASS
LENS	CLEAR FLAT TEMPERED
SOCKET	BI PIN
LAMP	MR16
MAX LAMP	35W
VOLTAGE	12V AC/DC
PROJECTION	UP TO 35 FT
MAX DEPTH	UP TO 6 FT

STEP 1 FIXTURE CONFIGURATION

H20-502B

LEAD OPTION

- 50 50 FT LEAD
- 100 100 FT LEAD

*Standard Lead is 25 FT
Leave empty if you want standard option

STEP 2 LED LAMP CONFIGURATION

LED-MR16

LED WATTAGE

- 3.5W 280 LM
- 4.5W 320 LM
- 5.5W 420 LM

KELVIN TEMPERATURE

- 27K 2700K
- 30K 3000K
- 41K 4100K
- 55K 5500K

BEAM ANGLE

- 15D 15° NARROW *
- 45D 45° STANDARD
- 60D 60° WIDE**

Revised 08/18

INSTALLATION NOTE: It is important to hand tighten and seal this fixture with silicone before placing the fixture into water. For added protection - Apply silicone around the outside of the front cap and the bottom cord exit.

* Dimmable: See [MR16 LED Lamps Spec Sheet](#) for additional details
* Available in 45° only
** Available in 3.5w & 5.5w, 3000K only