

PROJECT	DATE
TYPE	CATALOG #

E26 ARCHITECTURAL STRING BK-E26




STRING DIMENSIONS




+ String and lamps are sold separately

SOCKET DIMENSIONS



SOCKET TOP VIEW



KEY FEATURES

- **·UV RESISTANT MATERIALS**
- •PVC SOCKET FORMS A TIGHT WATER SEAL
- **•COMMERCIAL GRADE**
- **·SPECIFY CUSTOM CUTS BY THE FOOT**
- ·FIELD CUTABLE BETWEEN SOCKETS
- •2 YEAR LIMITED WARRANTY
- **•ETL LISTED**
- •INTENDED FOR LAMP-DOWN APPLICATIONS ONLY
- *Check with local building and safety inspectors for specific requirements
- **Lightcraft recommends the use of guy wire for runs of 35' or more

PRODUCT SPECIFICATIONS

MATERIAL SPT-2
WIRE COLOR BLACK
WIRE GAUGE 16 AWG

SOCKET E26 (MEDIUM BASE)
MAX WATTAGE 25W PER SOCKET

12V MAX RUN 200 FT

120V MAX RUN 300 FT (1200 WATT MAX) SPACING 24" BETWEEN SOCKETS

VOLTAGE 12V OR 120V

12V WIRING DIRECT TO LOW VOLTAGE

TRANSFORMER

120V WIRING HARD WIRE OR SPECIFY POWER

PLUG (PART: BK-PWR-MALE)

CERTIFICATION ETL WET LOCATION



PROJECT	DATE
TYPE	CATALOG #

S14 LAMPS (OUTDOOR/INDOOR RATED)



Lightcraft Outdoor's LED Filament Collection offers a dimmable 1W vintage style filament LED with an antique 2400K warm white light output.

Available in 12VAC to easily integrate with your low voltage landscape lighting system. Also available in 120VAC.

12V FILAMENT LED



LED-BK-S14-1-12-FIL

WATTAGE 1W
KELVIN 2400K
LUMENS 45
DIMMABLE YES*
VOLTAGE 11V AC - 13V AC

BASE


120V FILAMENT LED



LED-BK-S14-1-120-FIL

WATTAGE 1W
KELVIN 2400K
LUMENS 100
DIMMABLE YES*
VOLTAGE 120V AC
BASE MEDIUM (E26)

S14 LAMP DIMENSIONS



Dimensions for all S14 lamps on this page.

*PRIMARY SIDE DIMMING: Requires LED magnetic low voltage (MLV) or LED electronic low voltage (ELV) dimmable transformer and compatible LED dimmer (MLV OR ELV) For more information see installation guidelines

MEDIUM (E26)

DECORATIVE BISTRO SHADES (FOR E26 NON SUSPENDED BISTRO STRING ONLY)

These shade options are ideal for customizing the look of the architectural bistro string. The shades also serve to achieve a DARK SKY design and avoid overhead light pollution.

PETAL SHADE



MODEL
DIMENSIONS
MATERIAL
OUTSIDE FINISH
INSIDE FINISH

BK-111-BZ 7-1/2"W X 3"H ALUMINUM BRONZE (BZ) WHITE REFLECTIVE

HAMMERED SHADE



MODEL BK-411-BZ
DIMENSIONS 8"W X 2"H
MATERIAL ALUMINUM
OUTSIDE FINISH BRONZE (BZ)
INSIDE FINISH WHITE REFLECTIVE



MODEL BK-511-BZ
DIMENSIONS 4-1/2"W X 2-3/4"H
MATERIAL ALUMINUM
OUTSIDE FINISH BRONZE (BZ)
INSIDE FINISH WHITE REFLECTIVE

⁺ Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers

^{*}LOW VOLTAGE SIDE DIMMING: Requires Lightcraft 12V In Line Dimmer



PROJECT	DATE
TYPE	CATALOG #

MOUNTING INSTALLATION ACCESSORIES

GALVANIZED AIRCRAFT CABLE



MODEL BK-CABLE-1/16 MATERIAL GALVANIZED DIAMETER 1/16" (7X7)

STRENGTH 480 LBS RATING ROLL SIZE 250 FT

MODEL BK-CABLE-1/8

MATERIAL GALVANIZED **DIAMETER** 1/8" (7X7) STRENGTH 1700 LBS RATING ROLL SIZE 250 FT

CABLE WIRE CLAMPS



MODEL BK-CABLE-CLAMP-1/16 MATERIAL GALVANIZED

MODEL BK-CABLE-CLAMP-1/8 MATERIAL GALVANIZED

WIRE TIES (SS)



MODEL BK-TIES-SS MATERIAL STAINLESS STEEL LENGTH 5" WIDTH 1/6" STRENGTH 150 LBS RATING QTY PACK 100


WIRE TIES (NYLON)





QTY PACK 100


MODEL BK-TIES-BK MATERIAL HEAVY DUTY NYLON LENGTH 8" WIDTH 1/3" STRENGTH 120 LBS RATING


DESIGN IDEAS (POSTS, POLES, HOOKS NOT SUPPLIED)
















PROJECT	DATE
ТҮРЕ	CATALOG #

SUBMITTAL SHEET

STEP 1 FIXTURE CONFIGURATION

LENGTH	MODEL
ft.	
Specify per foot	RK-E26 Standard Socket

STANDARD STRING CUT

- All bistro string comes in Black finish.
- Each string has 1ft. before the first socket with a pigtail for hard wire (12v or 120v).
- Each string has 1ft. after the last socket with a sealed looped end. FOR ADDITIONAL 12V LEAD (BK-LEAD) OR 120V POWER PLUG (BK-PWR-MALE) PLEASE SPECIFY IN STEP 2

STEP 2 LEAD CONFIGURATION

MODEL	LEAD LENGTH
	ft
BK-LEAD Lead Wire (per ft.)	Specify per foot
BK-PWR-MALE 8 ft. Male Plug	for BK-LEAD

LEAD ORDERING INFO

- All leads and power plugs are factory sealed and installed
- BK-PWR-MALE is for 120V installs at receptacles FOR ADDITIONAL 12V LEAD (BK-LEAD) OR 120V POWER PLUG (BK-PWR-MALE) PLEASE SPECIFY IN STEP 2

STEP 3 LAMP CONFIGURATION

QTY	MODEL
	12V OPTIONS LED-BK-S14-1-12-FIL 1W Filament LED - 2400K
	120V OPTIONS

LED-BK-S14-1-120-FIL 1W Filament LED - 2400K

STEP 4

SHADE OPTIONS

QTY	MODEL
	BK-111-BZ Petal Shade
	BK-411-BZ Hammered Shade
	BK-511-BZ Pyramid Shade

• All shades are Bronze (BZ) outer finish with white reflective inside finish.

STEP 5

ACCESSORY OPTIONS

QTY MODEL ft. BK-CABLE-GS-1/16 **BK-CABLE-GS-1/8** Sold by the foot QTY MODEL

BK-CABLE-CLAMP-1/16
BK-CABLE-CLAMP - 1/8
Sold individually

QTY	MODEL
	BK-TIES-SS
	Stainless Steel Cable Ties (100 QTY Pack)
QTY	MODEL
QTY	MODEL BK-TIES-BK