



ETL LISTED  
COMPLIES WITH UL1838

PROJECT	DATE
TYPE	CATALOG #

## UNIVERSAL PERFECTO

PATH LIGHT

AP-00B-03B / AP-00B-SHORT-03B

### KEY FEATURES

- SOLID BRASS
- TWO TIERED RIDGED SHADE
- NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- TEMPERED, SHOCK AND HEAT RESISTANT LENS
- HIGH TEMPERATURE CERAMIC SOCKET
- FIELD REPLACEABLE LED LAMP
- LIFETIME WARRANTY ON BRASS MATERIAL
- DIMMABLE+

### PRODUCT SPECIFICATIONS

MATERIAL	SOLID BRASS
FINISH	NATURAL BRONZE
LENS	FROST AND CLEAR INCLUDED
SOCKET	BI-PIN
LAMP	T3/G4
VOLTAGE	12V
LIGHT SPREAD	9-10 FT AVG
LEAD WIRE	3 FT

### STEP 1

#### FIXTURE CONFIGURATION

**AP-00B**

STEM OPTION

SHORT 15-3/4" STEM

TALL 22-3/4" STEM

SHADE

03B PERFECTO SHADE

FINISH

NBZ NATURAL BRONZE

### STEP 3

#### ACCESSORY OPTIONS

**AX-800P**

INCLUDED

STAKE OPTION

AX-802P HEAVY DUTY PERMA POST

### STEP 2

#### LED LAMP CONFIGURATION

**LED-T3**

LED WATTAGE

1.5W 110 LM

2.5W 210 LM

3.5W 280 LM

5W\* 400 LM

6W\* 480 LM

KELVIN TEMPERATURE

27K 2700K

30K 3000K

ENCAPSULATED

ENC ENCAPSULATED (IP67)

ONLY AVAILABLE IN  
1.5W, 2.5W & 3.5W

\* Dimmable: +Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers and LED lamps.

See [Encapsulated T3 LED Lamps Spec Sheet](#) for additional details (1.5w, 2.5w, 3.5w only)

\* 5w & 6w: Only available in Non-Encapsulated - (Non-Dimmable)