



PROJECT	DATE
TYPE	CATALOG #

UNIVERSAL LUCE 5

PATH LIGHT

AP-00B-111B / AP-00B-SHORT-111B

KEY FEATURES

- SOLID BRASS
- SMOOTH SHADE
- NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- HIGH TEMPERATURE CERAMIC SOCKET
- FIELD REPLACEABLE LED LAMP
- LIFETIME WARRANTY ON BRASS MATERIAL
- DIMMABLE+

PRODUCT SPECIFICATIONS

MATERIAL	SOLID BRASS
FINISH	NATURAL BRONZE
LENS	FROST AND CLEAR INCLUDED
SOCKET	BI-PIN
LAMP	T3/G4
VOLTAGE	12V
LIGHT SPREAD	8 FT AVG
LEAD WIRE	3 FT

STEP 1

FIXTURE CONFIGURATION

AP-00B

STEM OPTION

SHORT 15-3/4" STEM

TALL 22-3/4" STEM

SHADE

111B LUCE 5 SHADE

FINISH

NBZ NATURAL BRONZE

STEP 2

LED LAMP CONFIGURATION

LED-T3

LED WATTAGE

1.5W 110 LM

2.5W 210 LM

3.5W 280 LM

5W* 400 LM

6W* 480 LM

KELVIN TEMPERATURE

27K 2700K

30K 3000K

ENCAPSULATED

ENC ENCAPSULATED (IP67)

ONLY AVAILABLE IN 1.5W, 2.5W & 3.5W

STEP 3

ACCESSORY OPTIONS

AX-800P

INCLUDED

STAKE OPTION

AX-802P HEAVY DUTY PERMA POST

* Dimmable: +Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers and LED lamps.

See Encapsulated T3 LED Lamps Spec Sheet for additional details (1.5w, 2.5w, 3.5w only)

* 5w & 6w: Only available in Non-Encapsulated - (Non-Dimmable)