



PROJECT	DATE
TYPE	CATALOG #

## STARLIGHTER PERFORATED HANGING PENDANT

### H-108B

#### KEY FEATURES

- SOLID BRASS
- ALLOWS LIGHT THROUGH PERFORATIONS
- NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- TEMPERED, SHOCK AND HEAT RESISTANT LENS
- HIGH TEMPERATURE CERAMIC SOCKET
- FIELD REPLACEABLE LED LAMP
- LIFETIME WARRANTY ON BRASS MATERIAL
- DIMMABLE+

#### PRODUCT SPECIFICATION

MATERIAL	SOLID BRASS
FINISH	NATURAL BRONZE
SOCKET	BI PIN
LAMP	MR16/T3/FLICKER
VOLTAGE	12V
VISUAL PROJECTION	UP TO 40 FT
CHAIN/LEAD	3 FT

#### MR-16 INSTALLATION

Best for directional/task downlighting



#### T3/G4 INSTALLATION

Best for a decorative soft illumination with no hot spots.

#### FLICKER INSTALLATION

Best for a romantic flickering effect.





PROJECT	DATE
TYPE	CATALOG #

**STEP 1  
FIXTURE CONFIGURATION**

**H-108B** **NBZ**

FINISH ————

**NBZ** NATURAL BRONZE

**STEP 2  
MOUNTING OPTION**

**AX-803B-LOOP\***  
HANGING LOOP MOUNT



\* Sold Separately

**STEP 3  
LED LAMP CONFIGURATION**

**LED-MR16** [ ] [ ] [ ]

LED WATTAGE ————

3.5W 250 LM  
4.5W 350 LM  
5.5W 430 LM

KELVIN TEMPERATURE ————

27K 2700K  
30K 3000K

BEAM ANGLE ————

15D 15° NARROW \*\*  
45D 45° STANDARD  
60D 60° WIDE

**STEP 3  
LED LAMP CONFIGURATION**

**LED-T3** [ ] [ ] [ ]

LED WATTAGE ————

1.5W 110 LM  
2.5W 210 LM  
3.5W 280 LM

KELVIN TEMPERATURE ————

27K 2700K  
30K 3000K

FLICKER OPTION ————

**FLK** ONLY AVAILABLE IN  
1W 27K

+ Dimmable: See [MR16 LED Lamps Spec Sheet](#) for additional details  
\*\* Available in 3.5w & 5.5w

+ Dimmable: See [Encapsulated T3 LED Lamps Spec Sheet](#) for additional details (1.5w, 2.5w, 3.5w only)  
+ Flicker: Non-Dimmable