



PROJECT	DATE
TYPE	CATALOG #


NEPTUNE

MR16 UNDERWATER LIGHT

H20-502B

KEY FEATURES

- HEAVY CAST BRASS
- ADJUSTABLE FOR PRECISE LIGHT PROJECTION
- 25 FT UNDERWATER RATED SJW CORD
- 50 FT & 100 FT SJW CORD LEAD OPTIONS
- HIGH TEMPERATURE SOCKET
- FIELD REPLACEABLE LED
- DIMMABLE*



PRODUCT SPECIFICATION

MATERIAL	CAST BRASS
FINISH	NATURAL BRASS
LENS	CLEAR FLAT TEMPERED
SOCKET	BI PIN
LAMP	MR16
VOLTAGE	12V
PROJECTION	UP TO 35 FT
LEAD WIRE	25' (STANDARD), 50', 100'
MAX DEPTH	UP TO 6 FT

STEP 1

FIXTURE CONFIGURATION

H20-502B

LEAD OPTION

- 50 50 FT LEAD
- 100 100 FT LEAD

*Standard Lead is 25 FT
Leave empty if you want standard option

STEP 2

LED LAMP CONFIGURATION

LED-MR16

LED WATTAGE

- 3.5W 250 LM
- 4.5W 350 LM
- 5.5W 430 LM

KELVIN TEMPERATURE

- 27K 2700K
- 30K 3000K

BEAM ANGLE

- 15D 15° NARROW *
- 45D 45° STANDARD
- 60D 60° WIDE

* 15° Only available in 3.5w and 5.5w - 2700k or 3000k

+Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers and LED lamps.

Revised 08/18

INSTALLATION NOTE: It is important to hand tighten and seal this fixture with silicone before placing the fixture into water. For added protection - Apply silicone around the outside of the front cap and the bottom cord exit.