




·ANGLED SHROUD



·FLAT SHROUD



ETL LISTED
COMPLIES
WITH UL1838
Intertek

PROJECT	DATE
TYPE	CATALOG #

ARCHITECT PATH

BRASS ADJUSTABLE PATH LIGHT

PS-501B

KEY FEATURES

- CONTEMPORARY DESIGN
- COMES W/BOTH FLAT AND ANGLED SHROUDS
- SOLID BRASS
- NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- TEMPERED, SHOCK AND HEAT RESISTANT LENS
- HIGH TEMPERATURE CERAMIC SOCKET
- FIELD REPLACEABLE LED LAMP
- DIMMABLE+

PRODUCT SPECIFICATIONS

MATERIAL	SOLID BRASS
FINISH	NATURAL BRONZE
LENS	CLEAR FLAT TEMPERED
SOCKET	BI PIN
LAMP	MR16
VOLTAGE	12V
PROJECTION	UP TO 50 FT
LEAD WIRE	3 FT

STEP 1

FIXTURE CONFIGURATION

PS-501B

FINISH OPTION

NBZ NATURAL BRONZE

STEP 3

ACCESSORY OPTIONS

AX-800P

INCLUDED

STAKE OPTION

AX-802P HEAVY DUTY PERMA POST

STEP 2

LED LAMP CONFIGURATION

LED-MR16

LED WATTAGE

3.5W 250 LM

4.5W 350 LM

5.5W 430 LM

7W 500 LM

KELVIN TEMPERATURE

27K 2700K

30K 3000K

BEAM ANGLE

15D 15° NARROW *

45D 45° STANDARD

60D 60° WIDE

* 15° Only available in 3.5w and 5.5w - 2700k or 3000k

+Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers and LED lamps.

Coordinating Accent Light Series (FL-501B) also available