

PROJECT	DATE
ТҮРЕ	CATALOG #

150W TRANSFORMER

MULTI-TAP SS PRO SERIES TR-150-1215-SS

KEY FEATURES

- •FULLY ENCAPSULATED TOROIDAL CORE THAT RUNS COOLER AND QUIETER
- *DIMMABLE WITH ANY MLV OR CL DIMMER, AS LONG AS DIMMER'S MIN. LOAD IS COVERED
- **•PRIMARY SIDE THERMAL PROTECTION**
- *SECONDARY SIDE MAGNETIC CIRCUIT BREAKERS
- **•TIMER AND PHOTOCELL PLUG-IN READY**
- ·304 STAINLESS STEEL
- ·SEALED. LOCKABLE AND REMOVABLE HINGED DOOR
- •THREE 1" KNOCKOUTS & ONE 2" KNOCKOUT
- •6' HEAVY DUTY POWER CORD
- •ETL LISTED TO UL 2108
- ·10 YEAR LIMITED WARRANTY

PRODUCT SPECIFICATIONS

DIMENSIONS $10^{-1}/_{8}$ "H X $5^{-3}/_{4}$ "W X $4^{-5}/_{8}$ "D

MATERIAL STAINLESS STEEL (304)

WATTAGE 150W

VOLTAGE TAPS 12VAC - 15VAC

INPUT VOLTAGE 120V



TIMER AND PHOTOCELL ACCESSORIES SOLD SEPARATELY

TRANSFORMER ACCESSORY OPTIONS

Control the transformer's ON/OFF times with this traditional manual timer.

Control the transformer's ON/OFF times with this astronomic digital timer. Automatically adjust to daylight savings time. Includes a battery backup.



ASTRONOMIC TIMER

MODEL TR-T-105
DIMENSIONS 3-1/8"W X 3-1/4"H X 1-7/8"D

The photocell automatically activates your transformer at sunset and disables it at sunrise. Can be used in combination with Manual or Astronomic Timers.



PHOTOCELL

MODEL TR-TP-102 DIMENSIONS 3"W X 3"H X 1-5/8"D



MANUAL TIMER

MODEL TR-T-101
DIMENSIONS 3"W X 3"H X 1-5/8"D